

## ATLANTIC SUPER SYNTECH ECOBOOST SAE 5W-20 C5

(Fuel Economy- Fully Synthetic)

### DESCRIPTION

ATLANTIC SUPER SYNTECH ECOBOOST SAE 5W-20 API SN is the highest quality, synthetic, multi-seasonal, midSAPS engine oil. It meets the latest ACEA C5 and API SN (Resource Conserving) requirements. Fuel Economy oil guarantees extended service periods.

### APPLICATIONS

ATLANTIC SUPER SYNTECH ECOBOOST SAE 5W-20 API SN is fully synthetic engine oil that provides the best protection against wear and deposits. The post-treatment systems for petrol engines, which are sensitive to the lubricants used and expensive to maintain, are also protected over the long-term thanks to the product's low phosphorus content. The 5W-20 grade reduces internal friction within the engine as much as possible so that it can deliver full power, while at the same time generating fuel savings.

ATLANTIC SUPER SYNTECH ECOBOOST SAE 5W-20 API SN with specification Ford WSS-M2C-948-B/A is particularly well-suited for use with Ford's petrol-powered engines (except the Ford Ka, Focus ST and Focus RS). This oil is perfectly adapted for petrol FORD1.0L EcoBoost 3-cylinders engines meeting the Ford 948-B/A specification.

### PERFORMANCE FEATURES AND BENEFITS

- Reduced environmental impact: Reduction in fuel consumption
- Protection for pollution-control systems: With its low phosphorus content, this lubricant also optimizes the way in which three-way catalytic converters operate, preventing them from getting damaged through poisoning. This reduces NOx, HC and CO in particular.
- Engine protection and cleanliness: This oil contains detergent and dispersive additives and offers the best possible protection in its category against wear and deposits.
- Easier cold starts: Easy cold starts due to its extreme fluidity at low temperature.
- Oil change intervals: To be modified based on the usage, please always refer to the car owner's manual.

### RECOMMENDATIONS / SPECIFICATIONS

International Standards: ACEA A1/B1, C5, API SN, CF, ILSAC GF- 5

Meets or exceeds: FORDWSS-M2C948-B, FORD WSS-M2C948-A, JAGUAR-LAND ROVER STJLR.03.5004

Recommended to all Americans/Japanese/Korean/European petrol vehicles with multi fuel use.



### TYPICAL TECHNICAL PROPERTIES

Viscosity Grade, SAE J300	5W-20
Product code	6003-9455INF
Density at 15°C, g/ml, ASTM D4052	0.851
Cold Cranking Viscosity(CCS), mPa s, ASTM D5293	4100@-30°C
Kinematic Viscosity at 40°C, mm <sup>2</sup> /s, ASTM D445	41.83
Kinematic Viscosity at 100°C, mm <sup>2</sup> /s, ASTM D445	8.08
Viscosity Index, ASTM D2270	171
Flash Point(COC), °C, ASTM D92	220
Pour Point, °C, ASTM D97	-45
Total Base Number (TBN)	8.0
HTHS Viscosity @ 150°C mPa.s, CEC L-36-A-97	≥2.6

Note: These characteristics are typical of current production. While future production will conform to current specification, variations in these characteristics may occur.

ATL/PDS/AL/045/1\*, 04.12.23, Page 1/1

\* supersedes all previous versions