

ATLANTIC FULLY SYNTHETIC ATF D VI

(Full Synthetic ATF)

DESCRIPTION

ATLANTIC FULLY SYNTHETIC ATF D VI is formulated with premium synthetic base stocks and advanced additive technology, and meets all the stringent requirements of General Motors' DEXRON®-VI specification, which is designed for the modern automatic transmissions in GM vehicles. ATLANTIC FULLY SYNTHETIC ATF D VI can be used in new and old GM automatic transmissions & it is fully back-serviceable and can be used wherever DEXRON®-II and/or DEXRON®-III are recommended.

AFF DEXION VI

APPLICATIONS

ATLANTIC FULLY SYNTHETIC ATF D VI is high quality ATF suitable for use in automatic transmissions with torque convertors of passenger cars, as well as in wet clutches and power steering units.

PRODUCT BENEFITS

- Optimized frictional properties that provide smooth gear shifting during low temperature operation and help prevent transmission vibration
- Extends transmission fluid life and prevents fluid breakdown at higher operating temperatures
- Improved oxidation and thermal stability
- Reduces sludge and varnish build-up
- Outstanding low temperature performance

- Maintains lubricity
- · Thoroughly field tested
- Low viscosity formulation provides fuel economy benefits compared with fluids formulated to meet DEXRON®IIIH or earlier specifications.
- Improved anti-wear protection which contributes to extended transmission life
- Protects transmission gears and allows them to operate smoothly

RECOMMENDATIONS / SPECIFICATIONS

Meets or Exceeds General Motors DEXRON®-VI Requirements & for 2006 and newer GM vehicles. Meets the performance requirements of MB 236.41, Allison C-4 & VOITH H55.6335xx.

TYPICAL TECHNICAL PROPERTIES

| Product code | 12714AT |
|---|---------|
| Color, VISUAL | RED |
| Density at 15°C, g/ml, ASTM D4052 | 0.847 |
| Kinematic Viscosity at 40°C, mm ² /s, ASTM D445 | 30 MAX |
| Kinematic Viscosity at 100°C, mm ² /s, ASTM D445 | 6 |
| Viscosity Index, ASTM D2270 | 150 MIN |
| Flash Point(COC), °C, ASTM D92 | 200 MIN |
| Pour Point, °C, ASTM D97 | -45 MAX |
| Brookfield viscosity at -40°C, mPa.s, ASTM D2983 | 18,000 |

^{*} DEXRON® is a registered trademark of General Motors Corporation.

Note: These characteristics are typical of current production. While future production will conform to current specification, variations in these characteristics may occur.

ATL/PDS/ATF/005/02*, 01.12.23, Page 1/1
* supersedes all previous versions