

# ATLANTIC SYNTECH ENGINE OIL PSA PLUS SAE 0W-20 B712010

(Fully Synthetic Motor Oils)

## DESCRIPTION

ATLANTIC SYNTECH ENGINE OIL PSA PLUS SAE 0W-20 B712010 is a low SAPS ACEA C5 passenger car engine oil focused on the most recent Stellantis / PSA specification B71 2010, but also suitable for diesel and gasoline engines from other car manufacturers which require an ACEA C5 SAE 0W- 20 oil.

## APPLICATIONS

ATLANTIC SYNTECH ENGINE OIL PSA PLUS SAE 0W-20 B712010 is specifically designed for the most recent PSA GROUP (Peugeot/Citroën/DS) engines which require a PSA B71 2010 oil as Blue HDi, PureTech, hybrid engines, engines equipped with a Stop & Start system, etc. This ACEA C5 oil is also suitable for diesel and gasoline engines from other car manufacturers which require an ACEA C5 SAE 0W-20 oil.

## PERFORMANCE FEATURES AND BENEFITS

Aftertreatment protection: full aftertreatment device protection.

Cold start: excellent fluidity at low temperature.

Fuel economy: superior fuel economy and CO2 reduction.

## RECOMMENDATIONS / SPECIFICATIONS

International Standards : API SP, ACEA C5, C6

Meets or exceeds: FIAT 9.55535-DM1, PSA B71 2010, OPEL OV 040 1547 - A20

Meets quality requirements of most gasoline engine manufacturers in the USA, Europe, Japan and Korea

## TYPICAL TECHNICAL PROPERTIES

Viscosity Grade, SAE J300	0W-20
Product code	6895A-WL-20
Density at 15°C, g/ml, ASTM D4052	0.845
Cold Cranking Viscosity(CCS), mPa s, ASTM D5293	5700@-35°C
Kinematic Viscosity at 40°C, mm <sup>2</sup> /s, ASTM D445	40
Kinematic Viscosity at 100°C, mm <sup>2</sup> /s, ASTM D445	8.0
Viscosity Index, ASTM D2270	177
Flash Point(COC), °C, ASTM D92	230
Pour Point, °C, ASTM D97	-48
Total Base Number, mg KOH/g, ASTM D2896	9.4

Note: These characteristics are typical of current production. While future production will conform to ATLANTIC'S specification, variations in these characteristics may occur.

ATL/PDS/AL/079/01\*, 10.06.24, Page 1/1  
\* supersedes all previous versions

