

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: TITAN GT1 FLEX 34 5W-30

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Lubricant

Uses advised against: No uses advised against identified.

1.3 Details of the supplier of the safety data sheet

Manufacturer / Supplier FUCHS LUBRICANTS (UK) PLC.

New Century Street ST1 5HU Hanley

Telephone: +44 (0) 1782 203700

Contact Person: Product Safety department

E-mail: product.safety@fuchs.com Telephone: +44 (0) 1782 203700

1.4 Emergency telephone number: UK NHS: Dial 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

The product has not been classified as hazardous, but needs to be labelled according to regulation GB-CLP.

Classification according to GB-CLP.

Hazard summary

Physical Hazards: No data available.

2.2 Label Elements

EUH210: Safety data sheet available on request.

2.3 Other hazards: By handling of mineral oil products and chemical products no particular

hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept. The product may not be released into the envi-

ronment without control.

Issue Date: 19.02.2019 Revision Date: 20.12.2022 Print date: 14.06.2023

SDS_GB - EN - 000000000602015853

Version: 1.3



Product name: TITAN GT1 FLEX 34 5W-30

SECTION 3: Composition/information on ingredients

3.2 Mixtures

General information: Mixture containing severely refined base oils and additives.

Chemical name	Identifier		UK-REACH Regis- tration No.	Notes
mineral oil	EINECS: 265-157-1	50,00% - <100,00%		
alkarylamine, longchained	EINECS: 253-249-4	1,00% - <5,00%		
alkylphenol	EINECS: 406-040-9	1,00% - <5,00%		

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Classification

Chemical name	Identifier	Classification	
mineral oil	EINECS: 265-157-1	GBCLP: Asp. Tox. 1;H304	
alkarylamine, longchained	EINECS: 253-249-4	GBCLP: Aquatic Chronic 4;H413	
alkylphenol	EINECS: 406-040-9	GBCLP: Aquatic Chronic 4;H413	

GB-CLP

Please note that the mineral oils and petroleum distillates used in our products are severely refined and have a DMSO extract < 3% as measured by method IP 346 and are not classified as carcinogenic according to Note L of Annex VI of Regulation GB-CLP.

SECTION 4: First aid measures

General: Instantly remove any clothing soiled by the product.

4.1 Description of first aid measures

Inhalation: Supply fresh air; consult doctor in case of symptoms.

Eye contact: Promptly wash eyes with plenty of water while lifting the eye lids.

Skin Contact: Wash with soap and water.

Ingestion: Rinse mouth thoroughly.

4.2 Most important symptoms and effects, both acute and delayed:

May cause skin and eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Get medical attention if symptoms occur.

SECTION 5: Firefighting measures

Issue Date: 19.02.2019

Revision Date: 20.12.2022 Version: 1.3 Print date: 14.06.2023

SDS_GB - EN - 000000000602015853

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.



Product name: TITAN GT1 FLEX 34 5W-30

5.1 Extinguishing media

Suitable extinguishing me-

CO2, fire extinguishing powder or fog like water spraying. Extinguish larger fires with alcohol resistant foam or spray water with suitable surfactant add-

ed

Unsuitable extinguishing

media:

Water with a full water jet.

5.2 Special hazards arising from the substance or mixture:

During fire, gases hazardous to health may be formed.

5.3 Advice for firefighters

Special fire-fighting proce-

dures:

Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water inaccordance with official regulations. Collect contaminated fire fighting water separately. It must not enter

drains.

Special protective equipment for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be

worn in case of fire.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

In case of spills, beware of slippery floors and surfaces.

6.2 Environmental Precautions:

Prevent from spreading (e.g. by binding or oil barriers). Avoid release to the environment. Environmental manager must be informed of all major spillages. Prevent further leakage or spillage if safe to do so. Do not allow to enter drainage system, surface or ground water.

6.3 Methods and material for containment and cleaning

up:

tions:

Absorb with liquid-binding material (sand, diatomite, acidbinders, universal binders, sawdust). Dispose of the material collected according to regulations. Stop the flow of material, if this is without risk.

6.4 Reference to other sec-

See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on dis-

posal.

SECTION 7: Handling and storage:

7.1 Precautions for safe handling:

Prevent formation of aerosols. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products. Observe good industrial hygiene practices. Provide adequate ventilation.

7.2 Conditions for safe storage, including any incompatibilities:

Local regulations concerning handling and storage of waterpolluting products have to be followed. Do not heat up to temperatures close to the flash point.

Issue Date: 19.02.2019 Revision Date: 20.12.2022 Print date: 14.06.2023

SDS_GB - EN - 000000000602015853



Product name: TITAN GT1 FLEX 34 5W-30

7.3 Specific end use(s): No data available.

Storage Class: 10, Combustible liquids

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

Occupational Exposure Limits

None of the components have assigned exposure limits.

8.2 Exposure controls

Appropriate engineering

controls:

Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels below to the process to the level.

borne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information: Wash hands before breaks and after work. Use personal protective equip-

ment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be ad-

hered to inhandling the chemicals or the mineral oil products.

Eye/face protection: Avoid contact with skin and eyes. Goggles/face shield are recommended. If

risk of splashing, wear safety goggles or face shield. Avoid contact with skin and eyes. Goggles/face shield are recommended. If risk of splashing, wear

safety goggles or face shield.

Skin protection

Hand Protection: Material: Nitrile butyl rubber (NBR).

Min. Breakthrough time: >= 480 min

Recommended thickness of the material: >= 0,38 mm

Avoid long-term and repeated skin contact. Suitable gloves can be recommended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety directions. The exact break through time has to be found out by the manufactur-

er of the protective gloves and has to be observed.

Other: Do not carry cleaning cloths impregnated with the product in trouser pock-

ets. Wear suitable protective clothing.

Respiratory Protection: Ensure good ventilation/exhaustion at the workplace. Avoid breathing va-

pour/ aerosol.

Thermal hazards: Not known.

Issue Date: 19.02.2019 Revision Date: 20.12.2022 Print date: 14.06.2023

SDS_GB - EN - 000000000602015853

Version: 1.3



Product name: TITAN GT1 FLEX 34 5W-30

Hygiene measures: Always observe good personal hygiene measures, such as washing after

handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated foot-

wear that cannot be cleaned.

Environmental Controls: No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state: liquid Form: liquid

Color: Dark yellow Odor: Characteristic

pH: substance/mixture is non-soluble (in water)

Freezing point: not determined Boiling Point: not determined

Flash Point: 239 °C

Evaporation Rate: Not applicable for mixtures

Flammability (solid, gas): not determined

Flammability Limit - Upper (%)-:

Flammability Limit - Lower (%)-:

Vapor pressure:

Not applicable for mixtures

Not applicable for mixtures

Not applicable for mixtures

Not applicable for mixtures

Density: 0,85 g/cm3 (15 °C)

Solubility(ies)

Solubility in Water: Insoluble in water
Solubility (other): No data available.

Partition coefficient (n-octanol/water): Not applicable for mixtures

Autoignition Temperature:not determinedDecomposition Temperature:not determinedKinematic viscosity:65,44 mm2/s (40 °C)

Explosive properties:Value not relevant for classification
Oxidizing properties:
Value not relevant for classification

Particle characteristics: Not applicable

9.2 Other information No data available.

SECTION 10: Stability and reactivity

SDS_GB - EN - 000000000602015853

10.1 Reactivity: Stable under normal use conditions.

10.2 Chemical Stability: Stable under normal use conditions.

10.3 Possibility of hazardous Stable under normal use conditions.

reactions:

Issue Date: 19.02.2019

Revision Date: 20.12.2022 Version: 1.3 Print date: 14.06.2023



Product name: TITAN GT1 FLEX 34 5W-30

10.4 Conditions to avoid: Stable under normal use conditions.

10.5 Incompatible Materials: Strong oxidizing substances. Strong acids. Strong bases.

10.6 Hazardous Decomposition Thermal decomposition or combustion may liberate carbon oxides and oth-

Products: er toxic gases or vapors.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Oral

Product: Not classified for acute toxicity based on available data.

Specified substance(s)

mineral oil LD 50 (Rat): > 5.000 mg/kg

alkarylamine, long-

chained

LD 50 (Rat): > 5.001 mg/kg (OECD 423)

Dermal

Product: Not classified for acute toxicity based on available data.

Inhalation

Product: Not classified for acute toxicity based on available data.

Specified substance(s)

mineral oil LC 50 (Rat, 4 h): > 2.500 mg/l

Vapour

Skin Corrosion/Irritation:

Product: Based on available data, the classification criteria are not met.

Specified substance(s)

alkarylamine, long- OECD 404 (Rabbit):

chained Not irritant.

alkylphenol OECD 404 (Rabbit):

Not irritant.

Serious Eye Damage/Eye Irritation:

Product: Based on available data, the classification criteria are not met.

Specified substance(s)

alkarylamine, long- OECD 405 (Rabbit):

chained Not irritant.

alkylphenol OECD 405 (Rabbit):

Not irritant.

Issue Date: 19.02.2019 Revision Date: 20.12.2022 Print date: 14.06.2023

SDS_GB - EN - 000000000602015853

Version: 1.3



Product name: TITAN GT1 FLEX 34 5W-30

Respiratory or Skin Sensitization:

Product: Skin sensitizer: Based on available data, the classification criteria are not

Respiratory sensitizer: Based on available data, the classification criteria

are not met.

Specified substance(s)

alkarylamine, long-

chained No sensitizing effect (guinea pig); OECD 406

alkylphenol

No sensitizing effect (guinea pig); OECD 406

Germ Cell Mutagenicity

Product: Based on available data, the classification criteria are not met.

Carcinogenicity

Product: Based on available data, the classification criteria are not met.

Reproductive toxicity

Product: Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

Product: Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure

Product: Based on available data, the classification criteria are not met.

Aspiration Hazard

Product: Based on available data, the classification criteria are not met.

Other adverse effects: No data available.

SECTION 12: Ecological information

12.1 Toxicity

Acute toxicity

Product: Based on available data, the classification criteria are not met.

Fish

Specified substance(s)

LC 50 (Fish, 96 h): > 101 mg/l (OECD 203) alkarylamine, long-

chained

alkylphenol LC 50 (Fish, 96 h): > 74 mg/l (OECD 203)

Aquatic Invertebrates Specified substance(s)

SDS_GB - EN - 000000000602015853

alkarylamine, long-EC 50 (Water Flea, 48 h): > 101 mg/l (OECD 202)

chained

Issue Date: 19.02.2019 Revision Date: 20.12.2022

Version: 1.3 Print date: 14.06.2023



Product name: TITAN GT1 FLEX 34 5W-30

alkylphenol EC 50 (Water Flea, 24 h): > 101 mg/l (OECD 202)

Chronic Toxicity

Product: Based on available data, the classification criteria are not met.

Toxicity to Aquatic Plants Specified substance(s)

alkarylamine, long-

chained

EC 50 (Alga, 72 h): 600 mg/l (OECD 201)

12.2 Persistence and Degradability

Biodegradation

Product: Specified substance(s)

alkarylamine, long-

chained

Not applicable for mixtures

1 % (28 d, OECD 301B) Not easily biodegradable

alkylphenol (OECD 301B) Not readily degradable.

12.3 Bioaccumulative potential

Product:

Specified substance(s)

alkarylamine, long-

chained

Not applicable for mixtures

Bioconcentration Factor (BCF): 1.584

alkylphenol Oncorhynchus mykiss, Bioconcentration Factor (BCF): 260 (OECD 305) May

be accumulated in organism

12.4 Mobility in soil:

Product: Not applicable for mixtures

12.5 Results of PBT and vPvB

assessment:

The product does not contain any substances fulfilling the PBT/vPvB criteria.

12.6 Other adverse effects: No data available.

Water Hazard Class

(WGK):

WGK 1: slightly water-endangering.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

SDS_GB - EN - 000000000602015853

General information: Dispose in accordance with all applicable regulations.

Disposal methods: Do not empty into drains; dispose of this material and its container in a safe

way. When storing used products, ensure that the waste categories and

mixing instructions are observed.

Issue Date: 19.02.2019

Revision Date: 20.12.2022 Version: 1.3 Print date: 14.06.2023



Product name: TITAN GT1 FLEX 34 5W-30

List of Waste (LoW) Codes

13 02 05*: mineral-based non-chlorinated engine, gear and lubricating oils

SECTION 14: Transport information VDD/DID

ADR/RID	
14.1 UN number or ID number:	_
14.2 UN Proper Shipping Name:14.3 Transport Hazard Class(es)	_
Class:	Non-dangerous goods
Label(s):	_
Hazard No. (ADR): Tunnel restriction code:	_
14.4 Packing Group:	_
14.4 Facking Group. 14.5 Environmental hazards:	_
14.6 Special precautions for user:	_
IMDG	
14.1 UN number or ID number:	_
14.2 UN Proper Shipping Name:	_
14.3 Transport Hazard Class(es) Class:	Nan dangaraya saada
Label(s):	Non-dangerous goods
EmS No.:	_
14.3 Packing Group:	_
14.5 Environmental hazards:	_
14.6 Special precautions for user:	_
IATA	
14.1 UN number or ID number:	_
14.2 Proper Shipping Name:14.3 Transport Hazard Class(es):	_
Class:	Non-dangerous goods
Label(s):	-
14.4 Packing Group:	_
14.5 Environmental hazards:	_
14.6 Special precautions for user:	_

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

GB Regulations

The Ozone-Depleting Substances and Fluorinated Greenhouse Gases (Amendment etc.) (EU Exit) Regulations 2019:

none

Issue Date: 19.02.2019

SDS_GB - EN - 000000000602015853

Version: 1.3 Revision Date: 20.12.2022 Print date: 14.06.2023



Product name: TITAN GT1 FLEX 34 5W-30

The Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020:

none

15.2 Chemical safety as-

sessment:

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Revision Information: Vertical lines in the margin indicate an amendment.

Wording of the H-statements in section 2 and 3

H304 May be fatal if swallowed and enters airways.

H413 May cause long lasting harmful effects to aquatic life.

Other information: The classification complies with the current GB lists; however, it has been

supplemented with expert literature information and information provided by/about our company. The following evaluation methods were used: On the basis of test data; Calculation Method; Bridging Principle "Substantially simi-

lar mixtures"; Expert Judgement

Revision Date: 20.12.2022

Disclaimer: The data contained in this safety data sheet are based on our current

knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no sig-

nature.

Issue Date: 19.02.2019 Revision Date: 20.12.2022 Print date: 14.06.2023

SDS_GB - EN - 000000000602015853

Version: 1.3