

TITAN SYN SN 0W-16

Super High Performance, fuel-economy engine oil for a variety of petrol engines in passenger cars. Good cold starting behaviour and low oil consumption.

Description

TITAN SYN SN 0W-16 is an advanced all-season engine oil specially formulated for petrol engines providing very high fuel efficiency. Smooth cold start behaviour and fast engine lubrication is another advantage of TITAN SYN SN 0W-16. With its high temperature high shear viscosity of ≥ 2.3 mPas TITAN SYN SN 0W-16 perfectly services modern petrol engines from a variety of vehicle manufacturers.

Application

TITAN SYN SN 0W-16 is recommended for Hybrid Electric Vehicles (HEV) and Plug in Hybrid Electric Vehicles (PHEV) where an oil of this viscosity is recommended. TITAN SYN SN 0W-16 is also recommended for use in petrol and turbocharged petrol engines.

TITAN SYN SN 0W-16 is predominantly recommended for cars of American and Asian manufacturers, currently, including certain **Honda, Suzuki, Toyota and Lexus** models.

TITAN SYN SN SAE 0W-16 is miscible and compatible with conventional branded engine-oils. However, mixing with other engine oils should be avoided in order to fully utilize the product's benefits. As a result a complete oil change is recommended when converting to TITAN SYN SN 0W-16.

For information on product safety and disposal please refer to the latest Material Safety Data Sheet.

Advantages

- Recommended for Hybrid Electric (HEV) and Plug in Hybrid Electric (PHEV) vehicles.
- For use in normally aspirated and turbocharged petrol engines.
- Very good viscosity-temperature behaviour and highly shear stable ensures all-season use even under arduous conditions
- Reliable cold start and rapid oil circulation
- Very good wear protection
- Protects against engine sludge.
- Low oil consumption
- High fuel efficient based on viscosity and performance level
- Suitable for use in Honda, Toyota, Suzuki and Lexus models.

Specifications

- API SN Plus RC
- ILSAC GF-5

Product Information



Further Information

TYPICAL CHARACTERISTICS

Density @ 15°C	DIN 51757	0.845
SAE Grade	SAE J300	0W-16
Kinematic viscosity @ 40°C	DIN 51562-1	36.12
Kinematic viscosity @ 100°C	DIN 51562-1	7.27
Viscosity Index	DIN ISO 2909	171
Dynamic viscosity @ -35°C	DIN 51398	4824
Dynamic viscosity @ 150°C	CEC L-036-90	2.3
Flash point	DIN ISO 2592	234
Pour point	DIN ISO 3016	-39
Product dyeing	DIN 10964	None

Updated Nov 2019 ABUK

FUCHS LUBRICANTS (UK) plc
New Century Street, Hanley
Stoke-on-Trent, Staffordshire, ST1 5HU

Tel +44 (0)1782 203700
contact-uk@fuchs.com



Health, Safety and Environment - information is provided for products in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products.